

UHD 4K x 2K @ 30 Hz HDMI Audio De-Embedder/Extractor with Built-In HDMI Cable

MODEL NUMBER: P130-06N-AUDIO



Separates the audio track from an HDMI audio/video signal and sends it to a stereo receiver, speakers or other separate audio system. Ideal for connecting a Blu-ray player or other HDMI source to speakers with no HDMI input.

Description

The low-profile P130-06N-AUDIO UHD 4K x 2K HDMI Audio De-Embedder/Extractor is recommended for connecting an HDMI source, such as a Blu-ray™ player or desktop computer, to audio speakers that don't have an HDMI input. It separates the audio track from the HDMI signal and sends it directly to an alternate digital or analog system. It features 3.5 mm stereo and TOSLINK digital optical audio outputs to match most non-HDMI receivers and audio systems.

The P130-06N-AUDIO supports two-channel stereo and multi-channel audio up to 5.1 surround sound. It also supports uncompressed audio, such as LPCM, and compressed audio formats, including DTS® and Dolby Digital®. An LED indicates when the unit is receiving power, transmitting an audio/video signal or transmitting 5.1-channel surround sound.

On the video side, the HDCP 1.4-compliant P130-06N-AUDIO transmits UHD video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz. It supports 24-bit True Color (8 bits per channel) at 4K x 2K, 36-bit Deep Color (12 bits per channel) at 1080p, and optional 3D formats up to 300 MHz.

Connect the included USB Micro-B cable between the P130-06N-AUDIO and a USB port on the HDMI source or a USB charger to power the unit.

Features

Extracts Audio from an HDMI Signal and Sends It to a Separate Audio System

- Recommended for connecting HDMI source to speakers that don't have HDMI input
- 3.5 mm stereo and TOSLINK optical outputs connect to analog or digital non-HDMI audio equipment

Highlights

- Built-in 6 in. HDMI cable connects to audio/video source
- Supports multi-channel audio up to 5.1 surround sound
- Features 3.5 mm stereo and TOSLINK optical audio outputs
- Transmits UHD video resolutions up to 3840 x 2160 (4K x 2K)
- Powered via USB Micro-B connection

Package Includes

- P130-06N-AUDIO UHD 4K x 2K HDMI Audio De-Embedder/Extractor
- USB Micro-B cable, 3 ft.
- Owner's manual



- LED indicates the unit is receiving power or transmitting an audio/video signal
- Built-in 6 in. HDMI cable connects to audio/video source
- Included 3 ft. USB Micro-B cable provides power to the unit

Versatile Audio Options

- Supports 2-channel stereo and multi-channel audio up to 5.1 surround sound
- Supports uncompressed, such as LPCM, and compressed audio, including DTS and Dolby Digital

Vibrant UHD Video

- Transmits UHD video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz
- Supports 24-bit True Color (8 bits per channel) at 4K x 2K
- Supports 36-bit Deep Color (12 bits per channel) at 1080p
- Supports optional 3D formats up to 300 MHz
- Complies with HDCP 1.4 standards

Specifications

OVERVIEW	
UPC Code	037332200921
Technology	HDMI (All types); Stereo Audio; Toslink/SPDIF
INPUT	
Cable Length (ft.)	0.5
Cable Length (m)	0.15
Cable Length (in.)	6
PHYSICAL	
Shipping Dimensions (hwd / in.)	0.910 x 5.510 x 3.940
Shipping Dimensions (hwd / cm)	2.31 x 14.00 x 10.01
Shipping Weight (lbs.)	0.1300
Shipping Weight (kg)	0.06
Color	Black
CONNECTIONS	
Side A - Connector 1	HDMI (MALE)
Side B - Connector 1	HDMI (FEMALE)
Side B - Connector 2	TOSLINK (MALE)
Side B - Connector 3	3.5MM (FEMALE)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Side B - Connector 4	MICRO-USB B (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>