

## **Specification Sheet**

Part Number: 184-14003



High Density Slotted Wall Wiring Duct, 1" X 4", Non-Adhesive, PVC, White, 30ft/Box

Article Number	184-14003
Туре	SLHD1X4
Color	White (WH)
Features & Benefits	<ul> <li>Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. •Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.</li> <li>Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation. •Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.</li> </ul>
Quantity Per	box

**Product Description** 

Pro-Duct high density, slotted wall wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description	High Density Slotted Wall Wiring Duct, 1" X 4", Non-Adhesive, PVC, White, 30ft/Box
Global Part Name	SLHD1X4-PVC-WH
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.0
Width W (Metric)	25.4
Height H (Imperial)	4.07
Height H (Metric)	103.4
Mounting Hole Centers (Imperial)	2.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)

Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	EN 50085-2-3_1A CSA UL EN 50085-1:2005 + A1:2013
UL Recognized (US)	Yes
Package Quantity(Imperial)	30
Package Quantity (Metric)	9.14
Customs Number	3925900000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $<sup>\</sup>hbox{@}$  2018 HellermannTyton. All rights reserved.