

Specification Sheet

Part Number: CTP20STD



Convoluted Tubing, Slit, 2" Dia, PE, Black, 100 ft/carton

provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold

Article Number	169-60511
Туре	CTP20
Color	Black (BK)
Features & Benefits	• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture • Tubing protects cables and wires against automotive fluids, vibration wear • Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight
Quantity Per	carton
Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing,

and sunlight on cables and wires.

Short Description	Convoluted Tubing, Slit, 2" Dia, PE, Black, 100 ft/carton
Global Part Name	CTP20-PE-BK
Technical Description	Convoluted Tubing, Slit, 2" Dia., PE, Black
Length L (Imperial)	100.0
Length L (Metric)	30.4
Inner Diameter D (Imperial)	2.038
Inner Diameter D (Metric)	51.77
Diameter D (imperial)	2.388
Diameter D (metric)	60.66
Outside Diameter OD(Imperial)	2.388
Outside Diameter OD(metric)	60.66
Nominal Diameter (Imperial)	2.0
Nominal Diameter (Metric)	50.8
Wall Thickness WT (Imperial)	.011
Wall Thickness WT (Metric)	0.28

Material	Polyethylene (PE)
Material Shortcut	PE
Halogen free	No
Operating Temperature (Metric)	-40°F to +199°F (-40°C to +93°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	3926909987

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

^{© 2018} HellermannTyton. All rights reserved.